

Valves Using Neutral Position and Side Position (Special Two Position Valve)

In addition to the standard two positions valves (2B*), the following two types of two positions valves are available: valves with neutral position and pilot Y pressure position (2B*A), valves with neutral position and pilot X pressure position (2B*B).

Model Numbers	Graphic Symbols
04 DHG-06-2B* <u>A</u> 10	
DHG-* <u>-2B2A</u>	
DHG-* <u>-2B3A</u>	
DHG-* <u>-2B4A</u>	
DHG-* <u>-2B40A</u>	
DHG-* <u>-2B5A</u>	
DHG-* <u>-2B6A</u>	
DHG-* <u>-2B60A</u>	
DHG-* <u>-2B7A</u>	
DHG-* <u>-2B9A</u>	
DHG-* <u>-2B10A</u>	
DHG-* <u>-2B11A</u>	
DHG-* <u>-2B12A</u>	

Model Numbers	Graphic Symbols
04 DHG-06-2B* <u>B</u> 10	
DHG-* <u>-2B2B</u>	
DHG-* <u>-2B3B</u>	
DHG-* <u>-2B4B</u>	
DHG-* <u>-2B40B</u>	
DHG-* <u>-2B5B</u>	
DHG-* <u>-2B6B</u>	
DHG-* <u>-2B60B</u>	
DHG-* <u>-2B7B</u>	
DHG-* <u>-2B9B</u>	
DHG-* <u>-2B10B</u>	
DHG-* <u>-2B11B</u>	
DHG-* <u>-2B12B</u>	

DHG-04-*-50/5090**

DIMENSIONS IN MILLIMETRES (INCHES)

Mounting Surface: ISO 4401-AD-07-4-A

Options

- **Models with Pilot Choke Valve**
DHG-04-***-C2
- **Models with Stroke Adj. (R*)**

Outside dimensions are the same as those of the main valve of Solenoid Controlled Pilot Operated Directional Valves (DSHG-04). See [page 405](#).

★ For Spring Offset Models (2B*, 2B*A), it functions as drain port. When that model is used, directly connect it to the reservoir.

Note: For the valve mounting surface dimensions, see the dimensional drawing of the sharable sub-plate on [page 401](#).